

GILLETTE GENERATORS

LEADER IN BRUSHLESS TECHNOLOGY

MODEL GPED-65EK

60 HERTZ

Heavy Duty, Long Lasting, Diesel Fueled, Portable Power for contractor and rental use. If you want clean, dependable emergency electric power, with the most reliable engines, then GEN-PRO is the right choice for you. These generator sets are made for the tough jobs where you need the reliability, and that good clean emergency power will be there, when you need it. This is exactly what you get, when you choose GEN-PRO, because of it's many heavy duty & exclusive features.



| GENERATOR MODEL | GPED-65EK |
|---|---|
| MAXIMUM KW POWER | 6.5 |
| PRIME KW POWER | 6.0 |
| PRIME AMPS 120 VAC | 42 |
| PRIME AMPS 240 VAC | 21 |
| GENERATOR REGULATION | 5 % VOLTAGE REGULATION WITH MECHANICAL ENGINE GOVERNOR |
| FREQUENCY REGULATION | 5 %, (3 HERTZ) FREQUENCY REGULATION ON ALL MODELS |
| ENGINE MODEL | KOHLER KD420 EPA/CARB TIER IV CERT. & 3 YEAR LIMITED WARRANTY |
| ENGINE START METHOD | 12 VOLT ELECTRIC START WITH BUILT-IN BATTERY CHARGER |
| ENGINE HP@ 3600 RPM | 9 HP INTERMITTENT USE, 8 HP CONTINUOUS USE |
| ENGINE DISPLACEMENT | 1 CYLINDER, 24.5 CU. IN. (401 CC) |
| ENGINE AIR CLEANER | HEAVY DUTY, LOW PROFILE, DUAL ELEMENT FILTERS |
| FUEL TANK GAL. (LITERS) | 4.0 GAL. (15 L.) METAL FUEL TANK WITH GAUGE, TWIST-CAP, & SLOSH VALVE |
| ENGINE OIL SYSTEM | FULL PRESSURE WITH SPIN ON OIL FILTER, 1.6QT OIL SUMP |
| LOW OIL PROTECTION | AUTOMATIC ENGINE SHUTDOWN PROTECTION AT LOW OIL LEVEL |
| db(A) AT 7 METERS | 78 |
| 3/4 LOAD RUN TIME (HRS) | 5.63 |
| FUEL USE, GAL/LTR/HR | 0.71 / 2.65 |
| MOTOR START POWER | 1 1/2 HP, CODE G ELECTRIC MOTOR |
| CRANE PICK-UP HOOK | OPTIONAL EQUIPMENT : CENTRAL PICK-UP ON TOP OF GEN-SET |
| 2-WHEEL DOLLY KIT | OPTIONAL EQUIPMENT : COMPLETE WITH (2) HANDLES AND "NEVER GO FLAT" WHEELS |
| MAINLINE CIRCUIT BREAKER AND RECEPTACLE GROUP | 25 AMP, DOUBLE POLE CIRCUIT BREAKER FOR 240 VAC, MAIN BREAKER, PLUS INDIVIDUAL 120 VAC PUSH BUTTON CIRCUIT BREAKER PROTECTING EACH 120 V. RECEPTACLES |
| HOUR METER | RUN TIME HOURS, PLUS (3) MAINTENANCE ALERTS: 25 HOUR CHANGE OIL, 25 HOUR CHANGE OIL FILTER, 25 HOUR SERVICE AIR FILTER |
| POWER RECEPTACLES | (4) NEMA 5-15R 120 VOLTS, AND (1) L-14-30R 240 VOLTS RECEPTACLES |
| PROTECTIVE ROLL FRAME | RUGGED 1-1/4" ROUND ROLL FRAME, PROTECTING ENTIRE GEN-SET |
| LENGTH, INCHES | 30.5 |
| WIDTH, INCHES | 24 |
| HEIGHT, INCHES | 23 |
| SHIP WEIGHT, LBS. | 239 |
| CU. FEET SHIP BOX | 12 |

SPC1-GPED-65EK-20130802

GILLETTE GENERATORS, INC. 1340 WADE DRIVE ELKHART, IN 46514 USA TEL. (574) 264 - 9639 WEB-SITE: http://www.gillettegenerators.com E-mail: sales@gillettegenerators.com FAX (574) 262 - 1840